

Important Safety Instructions

- Turn off all power to the Junction Box before making any electrical adjustments.
- Always disconnect the power before installing/replacing bulbs, during cleaning or maintenance.
- To avoid the risk of fire, do not exceed the recommended wattage.
- Consult a qualified, licensed electrician before installation.

To Assemble

1. Install the beveled mounting disc to the J-box using the supplied machine screw hardware (2X).
2. Feed the electrical wires through one all thread. Then, attach the all-threads to the main body and slide the drop rods (2X) over it, flush with the main body.
3. There should be 1/2" of all thread above the tubing covers. If not, loosen the set screw and adjust. Secure the all threads by tightening the set screw on the main body.
4. Slide the canopy onto the all threads until flush with the tubing covers. Tighten the provided lock washers and nuts to make a secure connection.
5. Connect the wires from the lavalier to those from the J-Box using the Wago wire connectors.
6. Push the ceiling plate over the mounting disc, flush with the ceiling and tighten the set screws (3X) using the supplied allen key.
7. Screw in the bulb (1X) and place the glass shade onto the shade holder. *DO NOT OVER TIGHTEN THE BULBS*
8. Place the fins shade over the glass shade.
Note: fins shade sits on top of the glass shade.
9. Turn on the power to confirm you have made good wire connections.

Care Instructions

- Wipe with a soft cloth. Do not use chemical cleaner.

*We recommend installation by a licensed electrician

