## **Important Safety Instructions**

- Turn off all power to the Junction Box before making any electrical adjustments.
- Always disconnect the power before installing/replacing bulbs, during cleaning or maintenance.
- To avoid the risk of fire, do not exceed the recommended wattage.
- Consult a qualified, licensed electrician before installation.

## To Assemble

- 1. Install the beveled mounting disc to the J-box using the supplied machine screw hardware (2X).
- 2. Hold the ceiling plate next to the J-Box, and connect the wires to those in the J-box using the Wago wire connectors.
- 3. Loosen each set screw (3X) at the 120° position on the flush mount ceiling plate.
- 4. Push the ceiling plate over the mounting disc, flush with the ceiling and tighten each set screw (3X).
- 5. Screw in each bulb (3X). \*DO NOT OVER TIGHTEN THE BULBS\*
- 6. Slide the shade (1X) over the bulbs and align it with the top cap. Screw in the bottom cap to secure the shade.
- 7. Turn on the power to confirm you have made good wire conections.

## Ceiling Plate Set Screw (3X) Top Cap Bulb (3X) (5) Shade (1X) (6) **Bottom Cap**

Mounting Disc

(1)(2)

## **Care Instructions**

• Wipe with a soft cloth. Do not use chemical cleaner.