

Important Safety Instructions

- Turn off all power to the Junction Box before making any electrical adjustments.
- Always disconnect the power before installing/replacing bulbs, during cleaning or maintenance.
- To avoid the risk of fire, do not exceed the recommended wattage.
- Consult a qualified, licensed electrician before installation.

To Assemble

1. Install the beveled mounting disc to the J-box using the supplied machine screw hardware (2X).
2. Feed the electrical wires through the all thread. Then, attach the all-thread to the main body and slide the drop rod over it, flush with the main body.
3. There should be 1/2" of all thread above the tubing cover. If not, loosen the set screw and adjust. Secure the all thread by tightening the set screw on the main body.
4. Slide the canopy onto the all thread until flush with the tubing cover. Tighten the provided lock washer and nut to make a secure connection.
5. Connect the wires from the pendant to those from the J-Box using the Wago wire connectors.
6. Push the ceiling plate over the mounting disc, flush with the ceiling and tighten the set screws (3X) using the supplied allen key.
7. Place one plastic washer (3X) onto the socket cover. Slide the shade (3X) over the socket cover. Place another plastic washer (3X) inside the shade and secure it by screwing in the threaded ring on the socket cover using the tool (provided). Repeat for all 3 pendants.
8. Screw in the bulb (3X).
 DO NOT OVER TIGHTEN THE BULBS
9. Turn on the power to confirm you have made good wire connections.

Care Instructions

- Wipe with a soft cloth. Do not use chemical cleaner.

*We recommend installation by a licensed electrician

